



NVR CCTV Surveillance
Network Video Recorder



HP-9404

Network Video Recorder

720P/1080P High Resolution





Features

- Support 4CH 1080P15fps or 2CH 1080P 30fps or 4CH 720P 30fps IP input.
- Intuitive and user-friendly Graphic User Interface(GUI), Windows style, operation by mouse
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Multi-mode recording: manual, timer, motion, sensor
- Playback: 4CH simultaneous playback
- Search: time/calendar, events(alarm, motion)
- Express and flexible backup via USB, network or DVD-RW(Sata)
- Pentaplex: live, record, playback, backup and remote operation
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- 4 PoE network ports, support IPC direct connection to NVR.
- Dual stream technology to encode recording stream and network stream respectively. User can adjust network stream to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- HDMI 1080P output
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting Windows phone, iPhone, Blackberry. Compatible with 3G
- Complete SDK function, easy to integrate with other applications

Specification

Model	HP-9404		
System	Compression	Standard H.264	
	CPU	Cortex A9 Dual Core	
	OS	Embedded Linux	
Video	Output	BNC 1	
		VGA x 1: 1080P(1920x1080)	
		HDMI x 1: 1080P(1920x1080)	
IP Input	1080P	4CH@15FPS	
		2CH@30FPS	
	720P	4CH@30FPS	
Audio	Input	-	
		Output	RCA x 1
			2-way audio
Record	Resolution	1080P/720P/D1	
	Frame Rate	1~25fps/CH(PAL) , 1~30fps/CH(NTSC)	
	Bit Rate	2M~12Mbps	
	Encode	VBR/CBR	
	Quality	6 Level	
	Mode	Manual, Timer, Motion, Sensor	
	File Manager	Lock, unlock, reserving time	
Playback	Playback	4CH	
	Search	Time/calendar search, event (motion, external alarm)	
	Smart Search	Apply different colors to display whether a channel in a period of time recording or not.	
	Function	Play, Pause, FF, FB, Digital zoom	
Alarm	Mode	Sensor, Motion, Video Loss	
	Input	4CH	
	Output	1CH	
	Triggering	Record, PTZ move, alarm out, e-mail, etc	
Network	Interface	RJ45 X 1	
	Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS	
	Others	18 users online, dual stream	
Cell phone	OS	iPhone, Blackberry, Andriod, Windows phone	
	Function	Multi-screen surveillance(for certain model),snapshot, PTZ control, save the device list	
Port	HDD	SATA x 1 Max. 4TB	
	RS485	RS485 x 1, support PTZ and keyboard	
	USB	USB2.0 2,one for mouse, another for USB backup device	
Others	External Remote Controller	Support	
	Power Supply	DC12V+DC48V	
	Dimensions	430mm * 300mm * 55mm (W*D*H)	
	WorkingEnvironment	0~50 °C , 10% ~ 90% Humidity	



NVR CCTV Surveillance Network Video Recorder