



NVR CCTV Surveillance
Network Video Recorder



HP-9408

Network Video Recorder

720P/1080P High Resolution





Specification



Features

- Support 8CH 1080P15fps or 4 1080P 30fps or 8 720P 30fps IP input.
- Intuitive and user-friendly Graphic User Interface(GUI), Windows style, operation by mouse
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Multi-mode recording: manual, timer, motion, sensor
- Playback: 8CH simultaneous playback
- Search: time/calendar, events(alarm, motion)
- Express and flexible backup via USB, network or DVD-RW(Sata)
- Pentaplex: live, record, playback, backup and remote operation
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Dual stream technology to encode recording stream and network stream respectively. User can adjust network stream to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- HDMI 1080P output
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting Windows phone, iPhone, Blackberry. Compatible with 3G
- Complete SDK function, easy to integrate with other applications

Model		HP-9408
System	Compression	Standard H.264
	CPU	Cortex A9 Dual Core
	OS	Embedded Linux
Video	Output	BNC 1
		VGA x 1: 1080P(1920x1080)
		HDMI x 1: 1080P(1920x1080)
IP Input	1080P	8CH@15FPS
		4CH@30FPS
	720P	8CH@30FPS
Audio	D1	8CH@30FPS
	Input	-
	Output	RCA x 1
Record	2-way audio	RCA x 1
	Resolution	1080P/720P/D1
	Frame Rate	1~25fps/CH(PAL) , 1~30fps/CH(NTSC)
Playback	Bit Rate	2M~12Mbps
	Encode	VBR/CBR
	Quality	6 Level
Alarm	Mode	Manual, Timer, Motion, Sensor
	File Manager	Lock, unlock, reserving time
	Playback	8CH
Network	Search	Time/calendar search, event (motion, external alarm)
	Smart Search	Apply different colors to display whether a channel in a period of time recording or not.
	Function	Play, Pause, FF, FB, Digital zoom
Cell phone	Mode	Sensor, Motion, Video Loss
	Input	8CH
	Output	1CH
Port	Triggering	Record, PTZ move, alarm out, e-mail, etc
	Interface	RJ45 X 1
	Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
Others	Others	18 users online, dual stream
	OS	iPhone, Blackberry, Andriod, Windows phone
	Function	Multi-screen surveillance(for certain model),snapshot, PTZ control, save the device list
HDD	HDD	SATA x 1 Max.4TB
	RS485	RS485 x 1, support PTZ and keyboard
	USB	USB2.0 2,one for mouse, another for USB backup device
External Remote Controller	External Remote Controller	Support
	Power Supply	AC110V/220V
	Dimensions	430mm * 300mm * 55mm (W*D*H)
WorkingEnvironment	WorkingEnvironment	0~50 ℃ , 10% ~ 90% Humidity



NVR CCTV Surveillance Network Video Recorder