



IP CAMERA SERIES
88SERIES



HD IP CAMERA

Water-proof Bullet Camera



Specification



Feature

- High resolution, image presented vivid and clear.
- Support automatic color change/IR-CUT, achieving day and night non-stop monitoring.
- Support various information superimposed (such as, ID, IP, DDNS and so on) convenient to operate
- Introduce advanced H.264 HP video compression, achieving ultra-low bit-rate, superb high-definition picture quality.
- Support dual-stream
- support various mobile long-distance monitoring, iPhone, Windows Mobile, BlackBerry, Symbian, Android
- Support multiple web browsers, IE, Chrome, Firefox, Safari
- support auto electronic shutter, adapt to different monitoring environment
- web and CMS supporting, central management software MYEYE, providing SDK development.
- support HVR/NVR connection, conform to ONVIF

Model	Hmp-88D13
Camera	
Image sensor	1/3" AR0130 CMOS
Min.illumination	Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR B/W 0.1 Lux @(F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)s to 1/10,000 s
Lens	HD Professional Lens 3.6mm/6mm/ F1.8
Lens mount	M12
Day/night	Support IR-CUT
Compression	
Video compression	H.264 HighProfile, JPEG snapshot
Bite rate	32 Kbps~8Mbps
Audio compression	G.711a
Image	
Max.image reolution	1280x960
Frame rate	50Hz: 25fps 60Hz: 30fps
Image setting	Saturation, brightness and contrast are adjustable through IE browser or client software.
Network	
Storage	local SD card storage(optional),network storage
Intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP (HTTPS,SIP ,802.1x,IPv6)
Basic	anti-flicker, dual-stream, heartbeat, password protection
Interface	
Network interface	1*RJ45 10M/100M adaptive ethernet port
LED	24Pc 10-20 Meters
Other	
Working condition	-10°C ~60°C / Humidity 90% (non-condensing)
Power supply	DC12V ±10%
Power consumption	IR3 : 6W MAX;
Protection range	IP66
IR distance	"IR1":30-40 meters;
Dimension	93mm.x68mm.
Weight	300g.